

For precision cutting at right angle !! **BAND SAW BEAVER SERIES**

For cutting steel pipe, conduit pipe, poly vinyl pipe, cast iron pipe, stainless steel pipe, steel material, square pipe, round bar, aluminum frame, etc.





Square Cut (Chain, Flat Vise)

Precise Cutting Feed

The adjustment device achieves precise cutting for various materials.

Adjustment

Ideal for precision cutting at right angle.

Bundle Cut (Chain Vise) Can cut a bundle of same

Band Saw Beaver 4 Eco Band Saw Beaver 6 Band Saw 8

materials.

For cutting steel pipes, H steel, square pipes, and round bars **Band Saw Beaver 4 Eco**

Code No.BB400-1							
Steel Pipe : ~ø130mm (4")	Chain Vise	Over-Load Protector					
High speed cut for better productivity Can cut a bundle of same materials. Easy to replace the saw blades from t	Movie						

Higher - grade cutting capacity up to ø130mm !!



	Steel pipe	ø130mm (4")
Cutting	H - Beam	100mm×100mm
Capacity	Square pipe	□100mm
	Round bar	ø60mm
W	eight	31kg
N	lotor	220-240V • 200W X Voltage made to order
Standard Accessories		14 TPI HSS (1pce): Code No.88915

For cutting steel pipes, H steel, square pipes, and round bars

Band Saw Beaver 4F Eco						
Code No.BB40F-1						
Steel Pipe : ~ø120mm (4")	Flat Vise	Angle Cut (until 45°)	Over-Load Protector			
High speed cut for better product Can cut a bundle of same materia	5		Movie			

Quick clamp system helps to set up material quickly !!



	Steel pipe	90°:ø120mm(4")	45°:ø50mm (2")	
Cutting	H - Beam	90°:100mm×100m	90°:100mm×100mm	
Capacity	Square pipe	90°: 🗆 100mm	45°∶□50mm	
	Round bar	90°:ø60mm	45°:ø50mm	
Weight		33kg		
М	otor	220-240V • 200W	※ Voltage made to order	
Standard Accessories		14 TPI HSS (1pce):	Code No.88915	





Angle Cut (Flat Vise)

Cuts material at right angle or mitre cuts from 0°up to 45°

Band Saw Beaver 4F Eco Band Saw Beaver 6F Band Saw 8F Band Saw 32F

Safety and Harmlessness

Cutting safely and harmlessly without sparks, cutting dust and noise.

Over-Load Protection

Protect a motor from burnout by over-load protection.

O Asada

For cutting steel pipes, H stee	el, square pipes, a	nd round bars	For cutting steel pipes, H steel, square pipes, and round ba		
Band Saw Beaver 6			Band Saw 8		
Code No.BB003-2	Code No.BB003-2			Hydraulic : Code No. BB80	
Steel Pipe : ~ø180mm (6")	Chain Vise	Over - Load Protector	Steel Pipe:~ø220mm(8")	Chain Vise	
Precise right angle cutting at high speed. Movie Easy to replace the saw blade from the front side. Can cut a bundle of same material.			Hydraulic type enables to adjust the c	precise cutting adjustment model, oil damper [Hydrau cutting speed steplessly. o prevent burning its motor.(Standard	

Higher durability with strain prevention rib !!



	Steel pipe	ø180mm (6")
Cutting	H - Beam	150mm×150mm
Capacity	Square pipe	□150mm
	Round bar	ø80mm
W	eight	42kg
M	lotor	220-240V • 200W X Voltage made to order
Standard Accessories		14 TPI HSS (1pce): Code No.70114

For cutting steel pipes, H stee	el, square pipes, ar	nd round bars
Band Saw 8		, 'UE VV
Standard Code No. BB800-3	Hydraulic [:] C	code No. BB800H-3
Steel Pipe : ~ø220mm (8")	Chain Vise	

ulic] type is available.

& Hydraulic)

Ideal for cutting at right angle !!



	Steel pipe	ø220mm (8")		
Cutting	H - Beam	200mm×150mm		
Capacity	Square pipe	□175mm		
	Round bar	ø100mm		
W	/eight	Standard : 52kg	Hydraulic : 54kg	
Ν	lotor	220-240V•200W	⅔ Voltage made to order	
Standard	Accessories	14 TPI HSS (1pce):	Code No.70446	

For cutting steel, H steel, square, and round pipes				For cutting steel pipes, H steel, square pipes, and round bars		
Band Saw Beaver 6F			Band Saw 8F			
Code No.BB103-2	Code No.BB103-2			Standard Code No. BB80F-3	Hydraulic [:] C	ode No. BB80FH-3
Steel Pipe : ~ø180mm (6") Flat Vise Angle Cut (until 45°) Over - Load Protector			Steel Pipe : ~ø220mm (8")	Flat Vise	Angle Cut (until 45°)	
Precise right angle cutting at high speed. Movie			In addition to the spring damper [Standard} type of p	precise cutting adjustment mod	el, oil damper [Hydraulic] type is available.	

Precise right angle cutting at high speed. Easy to replace the saw blade from the front side. Quick clamp system helps to set pipes quickly.



Quick clamp system helps to set up material quickly !!

Simple to replace saw blade with New Tension Handle. Frame falling down protection system assures safe work. Quick clamp system helps to set a material quickly.

Equipped with Over load protection to prevent burning its motor.(Standard & Hydraulic)

Hydraulic type enables to adjust the cutting speed steplessly.




	Steel pipe	90°:ø180mm(6")	45°:ø77mm (21/2")	
Cutting	H - Beam	90°:150mm×125n	าท	
Capacity	Square pipe	90°: 🗆 150mm	45°: 🗆 75mm	
	Round bar	90°:ø80mm	45°:ø75mm	
W	eight	47kg		
M	lotor	220-240V • 200W	※ Voltage made to order	
Standard	Accessories	14 TPI HSS (1pce):	Code No.70114	



	Steel pipe	90°:ø220mm(8")	45°:ø115mm(4")
Cutting	H - Beam	90°:200mm×150mm	45°:125mm×125mm
Capacity	Square pipe	90°: 🗆 175mm	45°∶□125mm
	Round bar	90°:ø100mm	45°:ø100mm
W	/eight	Standard : 61kg	Hydraulic : 63kg
N	/lotor	220-240V•200W %Vol	ltage made to order
Standard Accessories		14 TPI HSS (1pce) : Code N	No.70446

@Asada



	Steel pipe	90°:ø320mm(12")	45°:ø195mm (7")	
Cutting	H - Beam	90°:300mm×300mm	45°:200mm×200mm	
Capacity	Square pipe	90°: 🗆 300mm	45°: 200mm	
	Round bar	90°:ø150mm		
Weight		114kg		
Motor		220–240V•300W X Voltage made to order		
Standard Accessories		10 TPI HSS (1pce) : Code No.BS905		

Band Saw Blade

SK	HSS

For Band Saw Beaver 4 Eco • 4 F Eco Item Code No. Quantity SK 8 TPI 70078 10 SK 10 TPI 88916 10 SK 14 TPI 88887 10 SK 18 TPI 70077 10 SK 24 TPI 88888 10 SK 32 TPI 71069 10 HSS 8 TPI 70132 5 HSS 10 TPI 70075 5 HSS 14 TPI 88915 5 HSS 18 TPI 70603 5 HSS 24 TPI 70413 5 GRIT SAW 70141 5 For Band Saw Beaver 6 • 6F

Item	Code No.	Quantity
SK 8 TPI	70120	10
SK 10 TPI	70121	10
SK 14 TPI	70110	10
SK 18 TPI	70111	10
SK 24 TPI	70112	10
HSS 8 TPI	70133	5
HSS 10 TPI	70113	5
HSS 14 TPI	70114	5
HSS 18 TPI	70602	5
HSS 24 TPI	70257	5
GRIT SAW	70142	5

For Band Saw Beaver 8 • 8 F • 10

Item	Code No.	Quantity
SK 8 TPI	70439	10
SK 10 TPI	70440	10
SK 14 TPI	70441	10
SK 18 TPI	70442	10
SK 24 TPI	70443	10
HSS 8 TPI	70444	5
HSS 10 TPI	70445	5
HSS 14 TPI	70446	5
HSS 18 TPI	70493	5
HSS 24 TPI	70447	5

For Band Saw 32F

Item	Code No.	Quantity
HSS 4/6 TPI	BS912	3
HSS 6/10 TPI	BS911	3
HSS 10 TPI	BS905	3
HSS 14 TPI	BS946	3

O Asada

For cutting existing stainless steel pipes Movie Pipe Saw 200SP 민. Code No.PS201SP 92mm . (€□ Steel Pipe:1/2"~8" Stainless Steel Pipe:1/2"~8"** 93mm To cut installed pipes up to 8" fast and easily !! Easy to work in confined spaces such as under the roof. Reduction of working time with fast cutting. Very light weight-Only 3.9kg. 480mm FAST CUTTING SPEED CONTROLLER BUST GEAR STR W SPEEP START FI 1/2~8 1/2~4" (thickness: 4mm or less) 1/2~8" (thickness: 3mm or less) ess ATTOM STREET Stroke length 26mm 700~2,060 times/min Weight Motor 3.9kg Super HSS Blade 200×8TPI / 270×8TPI (each 1 pce), . Chain Vise, Wrench, Plastic case % For cutting 8", optional blade '320x6/8' is necessary.

For cutting existing	pipes and buried pipes for repairing	g & dismantling!!	and the former of the former
Pipe Saw	380SP	*****	- 302mm252mm
HSS:Code No.PS	Grit Sav	v:Code No. <mark>PS381SP</mark>	
Steel Pipe:2"~ Stainless Steel			
physical power.	to 14"!! enables to cut with less peed, also applicable to lastic pipes. tor and overload	of existing pipes, narrow space narrow space	612mm
Item	HSS	Grit Saw	
Code No.	PS386SP	PS381SP	C D D IL
Application	Steel pipe, Stainless steel pipe,	Water pipe for ductile cast iron and	
Steel	ductile cast iron 2~12" (14" Optional)	mortar lining cast iron	
Capacity Stainless	2~12"		
Motor	220-240V, 1,300W 50/60Hz		
Stroke length	57mm		
Weight	19kg Cow Blade UCC 280, 400mm (cook	Cauy Diada LICC 200, 400mm (see h	
Standard Accessories	Saw Blade HSS 380 • 490mm (each 1pce), Guide Plate 8"+12", Magnet- Attached Wedge (L), Ratchet Wrench, Case	Saw Blade HSS 380 • 480mm (each 1pce), Guide Plate 8"+12", Magnet- Attached Wedge (L), Ratchet Wrench, Case	
			臺

Blade Pipe Saw 165S • 200SP

Acoda mumminum , . 1

Blade for Pipe Saw 165S • 200SP (Super HSS)

Blade (HSS)

For Pipe Saw 165S • 200SP Cutting Capacity Code No. Quantity Item 140×8 TPI 61210 5 ~ 2" 200×8 TPI 61305 5 ~ 4" 200×6/8 TPI ~ 4" 61327 5 290×6/8 TPI 61337 5 ~6" 61471 5 320×6/8 TPI ~ 8"

※ Also avairable for Pipe Saw 150.

Autorin transmannan and and a

Item	Code No.	Quantity	Cutting Capacity
140×14 TPI	61369	5	~ 2"
140×6 TPI	61370	5	~ 2"
200×8 TPI	61371	5	~ 4"
200×6 TPI	61372	5	~ 4"
270×6 TPI	61458	5	~ 6"
270×8 TPI	61459	5	~ 6"
320×6/8 TPI	61486	5	~ 6"

% Super HSS includes cobalt. Also avairable for Pipe Saw 150. \$% Also avairable for Pipe Saw 150.

NAME OF A DESCRIPTION O

For Pipe Saw 300 • 350 • 350M • 380S • 350A

Item	Code No.	Quantity	Cutting Capacity
320×8 TPI	70310	5	~ 6"
380×8 TPI	70311	5	~ 8"
440×8 TPI	70278	5	~ 10"
490×8 TPI	70279	5	~12"
530×8 TPI	70295	5	~ 14"
640×8 TPI	70644	5	~16&18"
815×8 TPI	71099	5	~24"

Blade Grit Saw

. 4

Asada 1993.	GRIT SAW

For Pipe Saw 300 • 350 • 350M • 380S • 350A			
Item	Code No.	Quantity	Cutting Capacity
320	70288	5	~ 6"
380	70289	5	~ 8"
430	70260	5	~ 10"
480	70261	5	~ 12"
530	70262	5	~ 14"

12

@Asada

For cutting gas ductile iron, steel, reversal sealing pipes

Pipe Saw 400SA

Code No. PS401SA

Steel Pipe:2"~12" (24" Optional) Stainless Steel Pipe:2"~12"

No spark with Air motor!

Ideal for removing oil, gas, and water pipes. Air hose can be extended as you like. Rack&pinion system enables to cut with less physical power. Double insulated motor and overload protection system assure safe work.

Capacity	Steel	2~12" (24" Optional)
Gapacity	Stainless	2~12"
M	otor	Air motor 1,120W
Stroke	e length	57mm
Sp	eed	40~400 times/min
We	eight	21kg (body + vise)
Standard	Accessories	Saw Blade HSS 380•490mm (each 1pce), Guide Plate 8"+12", Magnet-Attached Wedge (L), Ratchet Wrench, Air maintenance unit, Casex2

For cutting water ductile iron, lining motor pipes

Pipe Saw 300/ 3	850 pat.
300:Code No. <mark>58003</mark>	350 : Code No. <mark>58013</mark>
300 : 2"~14"(18") 350 : 2"~14"	Flexible Shaft System

Flexible Shaft System. Ideal for cutting gas pipes!

Ideal for dismantling and assembling underground gas pipes.

Flexible shaft system eliminates the problem of sparks and makes it possible to cut pipes with water inside.

Compact and easy cutting with rack & pinion system.

Equipped with a low noise condenser motor allows you to work at night.

% To cut 18", optional accessories are necessary.

Item	Pipe Saw 300	Pipe Saw 350	
Code No.	58003	58013	
Power transmission	Flexible shaft system		
Stroke length	57mm		
Weight	57kg		
Motor	100V 750W % Voltage made to order		
Standard Accessories	HSS 320, 380, 490mm, Guide Plate 200AG • 300AG	Grit saw 320, 380, 430, 480, 530mm (1 pce each) Guide plate 250AW, 300AW, 350AW	

Blade HSS (for stainless)

- •

Guide Plate for Pipe Saw

For Pipe Saw 380S					
Item	Code No.	Quantity	Cutting Capacity		
440×8 TPI	70305	5	~ 10"		
490×8 TPI	70304	5	~ 12"		

For Pipe Saw 300 • 350 • 350A (※)				
	Size	Code No.	Applicable Pipe Saw balde	
	200AG	58524	Code No.70311	
	250AG	58703	Code No.70278 • 70305	
	300AG	58520	Code No.70279 • 70304	
	350AGW	58706	Code No.70295	
	400AGW	58528	Code No.70644	
	450AGW	58529	Code No.70644	
	450AGW	58529	Code No./0644	

For Pipe Saw 300 • 350 • 350A (※)				
	Size	Code No.	Applicable Pipe Saw balde	
	200AW	58711	Code No.70289	
	250AW	58521	Code No.70260	
	300AW	58522	Code No.70261	
	350AW	58523	Code No.70262	

For Pipe Saw 380S				
Size	Code No.	Applicable Pipe Saw balde		
200A	PS301	Code No.70311 • 70289		
250A	PS261	Code No.70278 • 70305 • 70260		
300A	PS262	Code No.70279 • 70304 • 70261		
350A	PS263	Code No.70295 • 70262		
400A	PS554	Code No.70644		
450A	PS347	Code No.70644		
600A	PS555	Code No.71099		

% Use Guide Plate applicable to maximum diameter.

Cold cutting for offshore oil & gas piping!!



